





# WIRE SHELVING ENCLOSURE SYSTEMS SWING DOOR INSTRUCTION MANUAL

## Parts Included:


- A. One (1) front swing door
- B. One (1) back panel **\*Has patent label**
- C. Two (2) side panels
- D. Two (2) rubber grommets
- E. One (1) door handle with (1) screw
- F. Two (2) door rings
- G. Two (2) Clear split vinyl tubing
- H. One (1) elastic cord with hook ends
- I. Clear panel clips for panel support





## Front View of Swing Door



## Top View Inside Shelf



## Open Door View w/ Elastic and Hook



## SIDE AND BACK PANEL INSTALLATION

*\*MUST INSTALL SIDES FIRST to make sure shelf is square*

1. Adjust shelves to correct height for enclosure. Make square on both sides.
2. Hold sides of panels with the bevel facing the shelf.
3. Insert top of panel behind upper shelf wire and push up between shelf sleeve and upper shelf wire as far as it will go. (Image 1)
4. Push bottom of panel over behind the lower shelf wire and push panel down. (Image 2)



Image 1



Image 2

⇒ If panel doesn't easily slip over bottom shelf wire, pound shelf down a bit using a rubber mallet.

*\* The panel should not show above the upper shelf wire or have a gap below the wire.*

⇒ *If the panel shows above the wire, pound the lower shelf down a bit using a rubber mallet.*

⇒ *If there is space below, pound the upper shelf down a bit.*

## FRONT DOOR PANEL

*\* Bevelled side of panel is the back of the door and should face the inside of shelf unit.*

⇒ **Doors can be installed to swing up or down.**

1. Insert screw (E) in hole through back of door (A), slide on washer and screw knob on tightly. (Image 3)
2. Insert grommets (D) on the front side through holes at top of front door.
3. Install door using the above method.
4. Open rings (F) and put through grommets and around upper shelf wire (see Diagram 1). Close rings to secure.
5. To open door, hold handle, push door upward and pull out door. To close door, push door up, place lower edge behind lower shelf wire, and push down into place.
6. Install elastic cord with hooks (H) by attaching to rings on inside of door. To hold door open, unhook one side, stretch cord over pole sleeve and hook to side of shelf (Image 4). This will hold door open for extended access.



Image 3




Image 4

⇒ If installing to swing down you do not need elastic cord.

## SECURE ENCLOSURE

1. Place Clear Split Vinyl Tubing (G) on support wires of lower shelf. Push back to allow front door panel to slip in place.
2. Open the Clear Plastic Clips (I) to make them easier to install.
3. With flat side up, push onto wire at top of panel. Press firmly until it snaps over wire and panel. (Image 5)
4. Repeat on bottom of each panel, flat side down, spacing clips every 6-10 inches.



Image 5

## TIPS

- ⇒ Applying a small piece of tape to the door rings (F) may help to keep them secure.
- ⇒ Panels may be cleaned with a soft cloth using glass cleaner or dish soap for grease.
- ⇒ Plastic Polish #1 can be used to renew and guard against static.
- ⇒ Zip ties have been provided to replace door rings if needed.



Made in the USA Pat. 6386657  
For replacement parts FAX (616) 844-1956  
e-mail: [info@chadko.net](mailto:info@chadko.net)